




ZenVox Dual Flavored Disposable Vape

Dual Tank 0.5ml*2

EmPower Your Oil & Brand to be the BEST.

Customized Device Settings for the BEST Oil Performance with Device Counterfeit Authentication.




Tel: 1 (720) **303-6806660**








Dimension (Picture and Description)





Dimension: 106 x 23 x 12mm

Appearance: There are no scratches, cracks, stains, uneven colors, unclear logos, and fades on the appearance of this product.

Features

- Button/Draw Activated
- Two Coils, Two Tanks
- Two Flavors & Blend Flavor
- Ceramic Heating Core
- Pure Flavor, Large Clouds
- High Cost-Performance
- Large Battery Capacity
- **Button Operation** 5 clicks on the button to turn on / off the device.









Dual tank | ZenVox



2 clicks to activate 15s preheat mode. 1 click to end preheat mode

Short Circuit Protection

Short circuit protection is triggered when the device is enabled. LED indicator flashes 3 times.

Timeout Protection

The device will stop working in case of exceeding 10 seconds. LED indicator flashes 2 times.

Out of Power

LED indicator flashes 10 times when the battery is too low, and there will be no response when the battery has completely run out.

Main Technical Parameter

Item	Parameter
Dimension	106 x 23 x 12mm
Volume	2 x 0.5ml
Heating Core Material	Ceramic
Mouthpiece Material	PC
Tank Type	PCTG
Center Post	SUS316L
Aperture Inlet	4 x Ø1.6mm
Resistance	2 x 1.6Ω
Activation	Button/Draw Activated
Power On/ Off	5 Clicks on the Button
Preheat Mode	2 Clicks on the Button
Battery Capacity	350mAh
Battery Housing	Aluminum
Output Voltage	3.0V



Dual tank | ZenVox



Charging Voltage	4.5v
Storage Temperature	23±5°C
Working Temperature	-10°C∼+50°C
Timeout Protection	Flash 2 Times
Short Circuit Protection	Flash 3 Times
Low Voltage Protection	Flash 10 Times
Overload Protection	Flash 3 Times
Charge Port	Type-C

How to Use

- To turn on/off the device, click on the button 5 times rapidly. The indicator light will stay on for 2 seconds to indicate on and flash 1 time for powering off. Once it is on, it's ready for use.
- To activate the Preheat Mode, click on the button 2 times rapidly. The breathing LED indicator fades in and out and runs at a low voltage of 1.8V. Preheat mode will last for 15 seconds. User can click one time to end the preheat mode.
- To switch the flavor, move the slide switch to either the left or right position for a single flavor; move the slide switch to the middle position to vape both two flavors at the same time

Filling Guide

1. Fill the tank with your cannabis oil.

Gently put the syringe into one of the tanks (between the airway and the outer wall of the oil tank) and fill the tank with oil at a proper speed, then fill the other one.

- ▲ Do not allow oil to enter the center airway!
- ▲ Do not top off the tank with oil.
- ▲ While filling oil, avoid dropping oil onto the shell to prevent chemical reactions. If so, please wipe it off immediately.

2. Press on the mouthpiece immediately after filling!



KUSHCART LLC





- ▲ Failure to insert the mouthpiece immediately after filling may cause leakage.
- ▲ We highly recommend using a capping machine or hand punch to press the mouthpiece.

6. Storage

- 1. The storage temperature is 23±5°C and the humidity is 50±10% RH.
- 2. Place in a cool, dark and ventilated place.
- 3. Keep the disposable sealed storage and avoid direct sunlight.

Notification

- 1. Press the mouthpiece into tank within 1 minute after filling.
- 2. Please fully charge the device before use.
- 3. Please keep the product out of the reach of children after use.
- 4. We highly recommend keeping your products upside down during transportation (with the mouthpiece facing down) to avoid oil leakage.

Customize available



